Pro Tuff Traffic Doors

www.worldmanufacturing.com | Call (800) 722-3539

Technical Specifications:

- 3/8" thick door panels.
- Steel bull-nose double-edged reinforcement for enhanced stability and quality.
- FDA-approved thick elastomeric coating with diamond-texture finish.
- Standard 13"X17" window per door panel.
 - o Option for larger windows.
- 3/16" thick polycarbonate shatter-proof window set in a high-impact urethane frame.
- Made with corrosion-resistant materials.
- Stainless steel hinges and mounting hardware included.
- Easy to open with less than a pound of pressure.

Single Panel Configuration



Custom widths up to 42" and custom heights up to 84" available

o i aranabic					
	Model #:	Opening Width	Opening Height	Weight	
	PRO3184S	31"	84"	52 lbs	
	PRO3684S	36"	84"	60 lbs	
	PRO4084S	40"	84"	67 lbs	



Galvanized door frames and other accessories are available. Consult page 15 for complete list of compatible accessories.

Features:

- Ideal for walk-through traffic.
- Popular option for restaurants, supermarkets, office and retail environments to separate kitchen or stock areas from customer areas.
- Available in custom sizes up to 84"X84".
- Door panels swing 180°.
- FDA-approved elastomeric coating resists scuffs, dings, and scarring.
- Easy to clean and sanitize with a damp cloth.
- Optional add-ons for larger windows, and installation anchors.
- All mounting hardware is included.
- Doors are crated for shipping.

Double Panel Configuration



Custom widths up to 84" and custom heights up to 84" available

04 available					
Model #:	Opening Width	Opening Height	Weight		
PRO3678D	36"	78"	61 lbs		
PRO3684D	36"	84"	65 lbs		
PRO4884D	48"	84"	87 lbs		
PRO6084D	60"	84"	109 lbs		
PRO7284D	72"	84"	131 lbs		
PRO8484D	84"	84"	152 lbs		

