

Ruff Tuff V-Cam Traffic Doors

www.worldmanufacturing.com | Call (800) 722-3539

Technical Specifications:

- 1½" thick door panels.
- Internally welded steel frame.
- Includes full perimeter gasketing.
- Panels are insulated.
- Comprised of hermetically sealed steel and tempered hard board.
- Extra thick elastomeric coating with diamond-texture finish.
- Standard 13"X17" window per door panel.
 - Option for larger windows.
- 3/16" thick polycarbonate shatter-proof window set in a high-impact urethane frame.
- Stainless steel V-Cam hinges come standard.

Features:

- Built to withstand maximum punishment from forklift and pallet-jack traffic.
- Available in custom sizes up to 96"X120".
- Door panels swing 180°.
- Steel-reinforcement makes our warp-proof V-Cam door the ideal candidate in wash-down environments and areas where salt-based chemicals are present.
- FDA-approved Elastomeric coating resists scuffs, dings, and scarring.
- All components are corrosion resistant.
- Easy to clean with a damp cloth.
- Vision light in each door panel.

Single Panel Configuration



Shown with optional Tear Drop Bumpers
Custom widths & heights available

Double Panel Configuration



Shown with optional Tear Drop Bumpers
Custom widths & heights available

Model #:	Opening Width	Opening Height	Weight
RTV3084S	30"	84"	106 lbs
RTV3684S	36"	84"	127 lbs
RTV4884S	48"	84"	170 lbs

Color Chart:



Model #:	Opening Width	Opening Height	Weight
RTV4884D	48"	84"	184 lbs
RTV6084D	60"	84"	230 lbs
RTV7284D	72"	84"	276 lbs
RTV7296D	72"	96"	315 lbs
RTV8496D	84"	96"	367 lbs
RTV9684D	96"	84"	367 lbs
RTV9696D	96"	96"	420 lbs

Galvanized door frames and other accessories available

