

Tuff Lite Stainless-Steel Doors

www.worldmanufacturing.com | Call (800) 722-3539

Technical Specifications

- 16 gauge thick (.0598 inches).
- 2½ pounds of 304 brushed stainless steel per square foot.
- 3/16" thick acrylic window with gasket comes standard in each door panel.
- Low-maintenance stainless steel auto-closing hinges included.
- Can be mounted with hinges on either left or right door jamb.
- Made in the USA.
- Limited 1-year warranty on parts.
- Doors are prefabricated with standard widths, but custom heights are available up to 84" high.

Features:

- Door panels swing 180°.
- Available in single panel and double panel configurations.
- 100% comprised of 304 brushed stainless steel.
- Heavy-duty auto-closing hinges allow doors to open with less than a pound of pressure.
- Stain and scratch resistant.
- Easy to sanitize. No coating to absorb microorganisms.
- Modern, elegant, timeless style.
- ABS Impact plates are available for extra durability.
- Easy to clean and sanitize using stainless steel cleaner and a microfiber cloth.

Single Panel Configuration



One door panel made to fit in your opening size.

| Actual Panel Width | Window Size | Opening Width | Opening Height |
|--------------------|-----------------|---------------|----------------|
| 29¼" | 9-3/8"X16-3/8" | 30" to 31" | 78" to 84" |
| 35¼" | 12-3/8"X17-3/8" | 36" | 78" to 84" |

Optional ABS Impact Plates ideal for push carts & heavier traffic areas.



Double Panel Configuration



Two door panels that split in the middle to add up to your opening

| Window Size | Opening Width | Opening Height |
|---------------------|---------------|----------------|
| (2) 8-3/8"X12-3/8" | 36" | 78" to 84" |
| (2) 8-3/8"X12-3/8" | 42" | 78" to 84" |
| (2) 8-3/8"X12-3/8" | 48" | 78" to 84" |
| (2) 9-3/8"X16-3/8" | 60" | 78" to 84" |
| (2) 12-3/8"X17-3/8" | 72" | 78" to 84" |

Galvanized door frames available

