

TECHNICAL SPECIFICATIONS

- 3/4" (0.75") Thick Door Panels
- Steel bull-nose double-edged reinforcement for enhanced stability & quality.
- FDA-approved thick elastomeric coating with diamond-texture finish.
- 3/16" thick polycarbonate shatter-proof window set in a high-impact urethane frame.
- Made with corrosion-resistant materials.
- Stainless Steel hinges & mounting hardware included.
- Easy to open with less than a pound of pressure.

FEATURES

- Door panels swing 180°.
- Ideal for walk-through traffic.
- Doors are crated for shipping.
- All mounting hardware is included.
- Available in custom sizes up to 72"X84".
- Easy to clean and sanitize with a damp cloth.
- Separate kitchen or stock areas from customer areas.
- Ideal for restaurants, supermarkets, office & retail environments.
- FDA-approved elastomeric coating resists scuffs, dings, and scarring.
- Optional add-ons for larger windows, and installation anchors.



INTERNALLY WELDED STEEL FRAME

Every door includes a welded steel frame for superior strength, longer life, and reliable performance.

SINGLE PANEL CONFIGURATIONS

Custom widths up to 36"
& custom heights
up to 84" available

Model #	Opening Width	Opening Height	Weight
PRO3184S	31"	84"	52 lbs
PRO3684S	36"	84"	60 lbs



ACCESSORIES



Galvanized door frames and other accessories are available. Call today for a complete list of compatible accessories.

DOUBLE PANEL CONFIGURATIONS

Custom widths up to 72"
& custom heights
up to 84" available

Model #	Opening Width	Opening Height	Weight
PRO3678D	36"	78"	61 lbs
PRO3684D	36"	84"	65 lbs
PRO4884D	48"	84"	87 lbs
PRO6084D	60"	84"	109 lbs
PRO7284D	72"	84"	131 lbs



AVAILABLE COLORS

