

RUFF TUFF V-CAM

Traffic Doors

**DURABLE SOLUTION
FOR HIGH-TRAFFIC AREAS**
Built for performance, cleanliness
and long-lasting reliability.

TECHNICAL SPECIFICATIONS

- 1½" thick door panels.
- Includes full perimeter gasketing.
- Panels are insulated.
- Comprised of hermetically sealed steel and tempered hard board.
- Extra thick elastomeric coating with diamond-texture finish.
- 3/16" thick polycarbonate shatter-proof window set in a high-impact urethane frame.
- Stainless steel V-Cam hinges come standard.

FEATURES

- Ideal candidate in wash-down environments and areas where salt-based chemicals are present.
- Built to withstand maximum punishment from forklift and pallet-jack traffic.
- FDA-approved Elastomeric coating resists scuffs, dings, and scarring.
- All components are corrosion resistant.
- Easy to clean with a damp cloth.

AVAILABLE COLORS



RUFF TUFF V CAM
Thickness: 1 Inch
Steel Reinforced Frame

INTERNALLY WELDED STEEL FRAME

Every door includes a welded steel frame for superior strength, longer life, and reliable performance.

Heavy-duty pivot-hinge designed to extend life of doors.

SINGLE PANEL CONFIGURATIONS

Custom widths up to 96"
& custom heights
up to 120" available



Model #	Opening Width	Opening Height	Weight
RTV3084S	30"	84"	106 lbs
RTV3684S	36"	84"	127 lbs
RTV4884S	48"	84"	170 lbs

ACCESSORIES

Galvanized door frames and other accessories are available. Call today for a complete list of compatible accessories.



DOUBLE PANEL CONFIGURATIONS

Custom widths up to 96"
& custom heights
up to 120" available



Model #	Opening Width	Opening Height	Weight
RTV4884D	48"	84"	184 lbs
RTV6084D	60"	84"	230 lbs
RTV7284D	72"	84"	276 lbs
RTV9684D	96"	84"	367 lbs

Model #	Opening Width	Opening Height	Weight
RTV7296D	72"	96"	315 lbs
RTV8496D	84"	96"	367 lbs
RTV9696D	96"	96"	420 lbs